

## 0.4 Symmetrical Cable (Pairing Stranded)

### Description

1/0.40 tinned copper conductor, insulated foam PE(skin-foam-skin), pairing with AL/polyester foil shield, tinned copper drain wire, PVC jacket

### Construction

TYPE	PAIR	CONDUCT O.D. (mm)	INSULATION O.D. (mm)	UNIT SHEATH O.D. (mm)	OUTER JACKET O.D. (mm)
SEYVP (V) 0.4-1P	1	1/0.4	1.0	-	2.8±0.2
SEYVP (V) 0.4-2P	2			2.8±0.2	6.9±0.3
SEYVP (V) 0.4-8P	8			2.8±0.2	10.2±0.3
SEYVP (V) 0.4-16P	16			2.8±0.2	14.6±0.3
SEYVP 0.4-8P	8			-	9.1±0.3

(V) --- indicated PVC unit sheathing.

### Characteristic

NOM. CAPACITANCE (pF/m)	NOM. IMPEDANCE @1MHz (Ω)	ATTENUATION @1MHz (dB/100m)
≤ 45	120±10%	≤ 2.6

### Color

PAIR	COLOR CODE		PAIR	COLOR CODE		PAIR	COLOR CODE		PAIR	COLOR CODE	
	A	B		A	B		A	B		A	B
1	white	blue	5	white	gray	9	red	brown	13	black	green
2	white	orange	6	red	blue	10	red	gray	14	black	brown
3	white	green	7	red	orange	11	black	blue	15	black	gray
4	white	brown	8	red	green	12	black	orange	16	yellow	blue